

# LED traffic advisor

The traffic advisor is optionally available with 4-7 lamp bodies. Through its amber light, the traffic advisor alerts subsequent traffic of dangers in all kinds of weather and visibility conditions.

## OPTIONS:

- installation optionally with 4-7 LED lamp bodies (amber)
- low power consumption (important for providing safety without being powered by a motor)

### Sputnik Compact



fig.: surface mounting



The control unit is not included in the scope of delivery.

<b>Technical data:</b>	
Housing:	Zing die casting, coated
Cover glass:	PC
Protection class:	IP65
Voltage:	12 V / 24 V multi voltage
Avg. Power consumption:	0,5 A at 12 V 0,3 A at 24 V
Permanent light	0,55 A at 12 V 0,34 A at 24 V
<b>Homologation: (Germany and international)</b>	
EMC after ECE-R 10:	(E) 10R-04 7591

Homologation as rear warning system; special approval for traffic advisor is required.

### Sputnik SL



The control unit is not included in the scope of delivery.

<b>Technical data:</b>	
Housing:	Sputnik SL
Voltage:	12 V / 24 V
Flash frequency:	> 2 Hz
Avg. power consumption:	12 V: 0.8 A (per LK) / 24 V: 0.6 A (per LK)
Type of protection:	IP6K7 / IPX9K
<b>Homologation: (Germany and international)</b>	
EMV nach ECE-R 10:	(E) 10R-05 6845