

Universal control unit

A selection of our control units is also available as universal version. These are freely configurable and can therefore serve any purpose. Differences are only made between the application areas "fire/emergency doctor" and "police".

The universal control units offer all the advantages of our standard control units. The buttons can be individually assigned and interlocked with the respective functions. Analogue outputs can be added.

It is also possible to choose favourites from a large selection of pre-programmed, application-specific texts in order to show them quickly and easily in the takedown display.

Variations of BE 308 Universal:



- BE 308 P Universal, 12 V
- BE 308 FN Universal, 12 V or 24 V

Technical data	
Weight:	140 g
Dimensions:	93 x 52 x 24 mm (WxHxD)

For more information, please contact our customer service.

Variations of BE 308 M Universal:



- BE 308 M - P Universal, 12 V

Homologation: (Germany and international) control units BE 300	
EMC according to ECE-R 10:	Ⓔ 10R-04 6703
Technical data	
Weight:	160 g
Dimensions:	180 x 52 x 24 mm (WxHxD)

Variations of BE 314 Universal:



Fig. FN

- BE 314 P Universal, 12 V
- BE 314 P Universal, 12 V

A selection of buttons/button laminations is included, more button caps available. Except for the basic buttons, all others are freely exchangeable and configurable.

Homologation: (Germany and international) control units BE 300	
EMC according to ECE-R 10:	Ⓔ 10R-04 6703

Technical data	
Weight:	160 g
Dimensions:	180 x 52 x 24 mm (WxHxD)

Variations of HBE 300 Universal:



Fig. FN

- HBE 300 P Universal 1, 12 V
- HBE 300 FN Universal, 12 V
- HBE 300 FN Universal, 24 V

Homologation: (Germany and international) HBE 300	
EMC according to ECE-R 10:	Ⓔ 10R-05 6932

Technical data	
Weight:	170 g
Dimensions:	66 x 124 x 24 mm (WxHxD)